MotoTec

Drifter 48v Electric Trike





WARNING Not for under 13 year old

Read this manual completely before rideing your electric trike

Motor power: 500 Watt Brushless Hub Motor

Battery: Four 12v 12ah Batteries (48v total)

Max Weight Capacity: 240 Lbs.

Recommende Age: 13 and up

Charger Included

Battery life: Over 300 charges

Rated Speed: 22 MPH (weight dependant)

Range per charge: 20-25 Miles*

Recharge time: 4-8hrs

Climbing Ability: 15 Degrees

Seat: Wide Saddle

Front Wheel Diameter: 70/90-14 78CM

Rear Tires Diameter: 10.4.5-5 27CM

Shipping Weight: 55KGS


Shipping Carton Size: 83*74.5*46CM

Scooter Weight: 93 Lbs

Scooter Dimensions: Length: 41 inches, Width: 28 inches,

Height: 50 inches

Ground Clearance: 2 inches



IMPORTANT!

BEFORE YOU OPERATE YOUR ELECTRIC SCOOTER PLEASE READ CAREFULLY:

YOUR EXISTING INSURANCE POLICY MAY NOT PROVIDE COVERAGE FOR ELETRIC VEHICLES; YOU SHOULD CONTACT YOUR INSURANCE AGENT TO DETERMINE IF COVERAGE IS PROVIDED.

Do not ride this scooter until you read and thorughly understand the owner's manual. If you have questions about the operation of this scooter, you should contat our service department.

It is extremely important that you follow the safety guidelines contained in this manual in order to insure maximum safety.

Failure to compiy with the standards outlined in this manual could result in fire and/or/serious injury.

We are not liable for any damage or injuries caused by unsafe or faulty repairs. Any repairs made to this product by unauthorized service technicians are the sole responsibility of the owner.

WARNING


PLEASE MAKE SURE THE QUICK RELEASE HAS BEEN LOCKED BEFORE DRIVING.
HANDLEBARS ASSEMBLE MUST OVER SAFETY VALVE AND MAKE SUER HAS BEEN LOCKED.

CHECK IF ALL TIRES ARE PROPERLY INFLATED BEFORE RIDING THE SCOOTER.

AL WAYS WEAR A HELMET WHEN RIDING THE SCOOTER. WEAR REFLECTIVE CLOTHING.

NEVER TRY STUNTS. AL WAYS MAINTAIN A SAFE SPEED.
FOLLOW ALL STANTE&CITY LAWS REGARDING USE OF ELECTRIC SCOOTER ON ROADS.

?



Our products are designed to be ecologically Conscious, please dispose of used batterise in Compliance with local laws..

WARNING

THE ELECTRIC TRISCOOTER IS NOT A TOY AND SHOULD NOT BEOPERATED BY ANY ONE UNDER 13YEARS OLD.

Safety Instruction(Please take not of the followings before each Ride.)

- . The maximum weight capacity is 300lbs.
- . Only one person at a time should ride.
- . Always wear protective gear including knee and elbow pads and an approved safety helmet when riding the scooter.
- . Betore riding be sure to check that all pivot points, locking buttons, quick releases, and latches are secured properly.
- .The power switch lock must be in the "off" position when the tri scooter is being charged.
- .Do not use the scooter when it is raining.
- .Do not place the battery near heat or fire.
- .Do not expose the charger near water.
- .Check if battery after each use.
- .Always ride on dry paved surfaces.Wet and uneven surfaces are a hazard.
- .Send and loose impediments are your enemy, avoid them.
- .Never operate too fast for your skills or condition.

LIST OF PARTS



- (1) handlebar
- (2) the front wheel motor
- (3) the seat
- (4) the rear wheels + drift ring
- (5) foot
- (6) flag
- (7) batteries, controller
- (8) Turn speed
- (9) brake



Are there on the pedal hint left and right





We need to use two screws to fixed Left and right pedal





We have total of 4 plugs ,so make sure Connect the same ABCD

ASSEMBLING THE ELECTRIC TRI SCOOTER

1. Unpack the Scooter carefully so that you do not misplace any of the parts.



2.Place the Scooter on a flat, level surface. Using any household item, raise the front base of the scooter up at least4 so you can easily connect the frame/front wheel to the base.



3.Remove the bolts and nuts from the connecting tubu clamp. Place the connecting tube into the top opening. After aligning the hole, place the two bolts through the connecting tube and neck assembly. Twist the bolts, do not hammer them through. Tighten these two bolts with the nuts provided.



ASSEMBLING THE ELECTRIC TRI SCOOTER

4. The two Allen set screws on the front of the connecting clamp are for removing any play after the bolts have been tightened. First, back of the nuts; second, set the screws; third, tighten the nuts to prevent the screws from backing off.



5.Match the pins of the plugs to the holes of the sockets.Note the alignment notches.













CHARGING THE BATTERIES

Before you ride the scooter for the first time, it is advised that the unit is to be fully charged(4-6 hours) and fully discharged (ride until the battery gauge indicates low battery) for at least three cycles to maximize the efficiency of the battery. After that, you should continue to charge the battery frequently, at least once every 30 days to prolong the battery lifespan.

IMPORTANT:

Do Not leave the battery uncharged for more than 3months; otherwise it will greatly reduce the battery lifespan.

TIP FOR BATTERU CARE: Charge the batter after each use! Option1:

To charge the batteries, plug the charger into the charge socket located on the rear side of the battry/controller compartment. Then plug the charge into a wall outlet.




Option2:(for professional use only)

Remove the screws from the battery compartment located at the front part of the footboard. Disconnect the wires. Life the battery box. Connect the battery and charger using the changer convertible cable. Plug the charger into the wall outlet.



RIDING THE TRI SCOOTER

Once you have completed the initial charge you are ready to ride.Remember, this is not a toy.The scooter can reach soeeds up to 15.5mph depending on the terrain and the weight of the rider.You must wear a helmet and protective pads.You must also be aware of all local laws and ordinances that govern and/or restrict the use of powered scooters.The laws and ordinances vary greatly from municipally. It is your responsibility to know and abide by your local restrictions.



To ride, plug the ket into ket ignition and turn the key

to the "ON"position. The battery gauge will illuminate indicating that the battery is in operation.

Hold onto the handlebars with both hands. Your left fingers will control the byakes and your right thumb will control the thumb throttle . As you depress the throttle lever with your thumb the speed will increase. Release the thumb throttle and apply the brake to stop the scooter. You will control the speed of the scooter by using both the throttle and the brake. When the brake handle is squeezed it cuts power to the throttle.

NOTE 1:You may use the balancing wheel(the smaller rear wheel) to balance the scooter when you want to ride with the front wheel raised.

WARNING:Never try stunts beyond the control of your skills. Never ride too fast for your skills or condition.

NOTE 2:When scooter is parked, press the power switch button, to the "OFF"position; this will avoid anyone from accidentally pushing the throttle causing the scooter to speed forward, Failure to do this could lead to an accident.

FOLDING THE TRI SCOOTER

- 1.Unplug the power connecting plugs.
- 2.Unscrew the bolts and nuts from the connecting tube clamp using the enclosed allen wrenches.
- 3.Life the connecting tube(which is also attachment to the handlebar tube).
- 4. Carefully place the handlebar tube on the footrest frame.
- 5. Finger screw the bolts an nuts back to the connecting tube clamp to avoid any misplacement.

MAINTENANCE

Battery:(for professional use only)

The scooter is powered by31Ah36V revhargeable batteries secured in a battery bag. Other than recharging ,these batteries need no maintenance. To prolong battery life, you must recharge the battery after each use. You must also charge your scooter if it has not been used for 30 days or more. If you must replace the batteries, they are located at the battery comparment at the footboard. To get them, remove the batteries with new ones and reconnect the wires. Follow the instructions on charging batteries to charge the new batteries.

TROUBLE SHOOTINNG GUIDE

(for professional use only)

| Dualdana | Course | Calution |
|-------------------------------------|-------------------------------|---|
| Problem | Cause | Solution |
| The power light | 1.Battery is | 1.Recharge your tri scooter. |
| by the thumb | discharged. | 2.Remove the screws that hold the |
| Throttle dose not | 2.Loose connection | battery compartment cover and |
| Illuminate when | inside the tri scooter | raise the cover.Visually inspect all |
| the tri scooter is | 3.Fuse us blown | there are no loose wires, |
| On | | reconnecting those that are. |
| | | 3.Replace the fuse. |
| The power | 1.The throttle handle | 1.Replace the throttle |
| Indicator by the | is not operating | handle.Contact your local dealer |
| Thumb throttle | properly. | to order a new throttle. |
| Illuminates but | | |
| Tri scooter still | | |
| Dose not work | | |
| Clicking noise | 1.Brush in motor | 1.Replace motor.Call your local |
| Coming from | has com loose | dealer to order a new 350W |
| Motor | 1103 COM 1003C | motor |
| | | |
| When the brake Lever is squeezed | 1.The brakes are not adjusted | 1.Adjust the brake by loosening the bolt on the rear brake wheel, |
| The tri scooter | properly. | Pull the cable and retighten the bolt. |
| Dose not stop. | ргорену. | T diff the casic and retighten the soft. |
| Scooter is losing | 1 Low bottom | 1 Decharge very better for 9berre |
| | 1.Low battery | 1.Recharge your battery for6-8hours |
| Speed. | 2.Battery is old. | 2.Replace battery.Call your local |
| | | Dealer to order a new 36V battery. |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| ' | | I |

DO NOT RETURN TO STORE

For service, Create Online, Trouble Ticket
Http://support.bigtoysusa.com